The Powerscreen® Metrotrak HA is a compact, high performance track mobile jaw crushing plant. With an aggressive crushing action and a high output even at tight settings, the Metrotrak is ideally suited for operators in the mining, quarrying and recycling industries.

The Metrotrak HA offers hydraulic adjustment which offers users the benefit of quickly and easily changing the size of finished product.

Options

### Features & Benefits

- · Heavy duty fabricated chassis and track frame
- Stepped self-cleaning grizzly feeder
- Fully skirted product conveyor Grizzly by-pass and fines chute
- Hydraulically folding feed hopper
- Dust suppression system
- · Economical to operate with a highly fuel efficient direct drive system
- Side conveyor • Single pole/twin pole magnet Radio remote control Belt weigher Hydraulically driven water pump Electric refuelling pump Wire mesh for underscreen Super tooth or multi tooth jaw plates
  - Sand & gravel Blasted rock River rock C&D waste Overburden Foundry waste Processed ores Processed minerals

Applications

**Output Potential** Up to 200tph (220 US tph)\*

Product Conveyor Width: 800mm (32")

## Crusher

Discharge height: 2.9m (9'6")

High capacity single toggle jaw Chamber size: 900mm x 600mm (35" x 23") Min CSS: 40mm (1.5")\* Max CSS: 100mm (4")\*



### **METROTRAK HA**

Weight (Est)	28,500kg (62,831lbs)
Transport width	2.4m (7'10")
Transport length	13.12m (43')
Transport height	3.3m (10'10")
Working width	3.87m (12'6") with side conveyor
Working length	13.1m (42'9")
Working height	3.4m (11'1")



\*Depends on application Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3/Stage 3A:, Tier 4i/Stage 3B:, Tier 4F / Stage 4).



# Power Unit

Tier 3/Stage 3A: CAT C7.1 ACERT 140kW (187hp) Fuel tank capacity: 400 L (106 US GAL) Tier 4F/Stage 4: CAT C7.1 142kW (190hp) Fuel tank capacity: 400 L (106 US GAL)



Tracks Width: 400mm (15.7")

