

1150 MAXTRAK

The high performance Powerscreen® 1150 Maxtrak is a medium sized cone crusher which has been designed for direct feed applications without pre-screening on clean rock. At its heart is the Automax® cone crusher which provides excellent reduction and product cubicity for the production of high quality aggregate and sub-base material. Hydraulic release capabilities are designed so that any uncrushable material entering the chamber is safely discharged.

Features & Benefits

- Renowned Automax® crusher technology
- Accepts clean all in feed
- Excellent product shape
- High reduction ratio
- Cone feed box level control to maintain choke feeding
- Hydraulic crusher setting
- Cone overload protection
- Heavy duty chassis and track frame
- Metal detector
- Dust suppression system
- Direct drive – Increased fuel efficiency and reduced operating costs

Options

- Concaves: extra coarse, medium coarse, fine
- Short throw eccentric
- Camera over crusher
- Feed hopper extension plates
- Product conveyor dust covers
- Product conveyor stockpile sensor
- Product conveyor belt weigher
- Cold climate oils
- Hot climate oils
- Hot climate coolers
- Urea re-fuelling pump
- Diesel re-fuelling
- Hydraulic water pump
- Radio remote control
- Lighting mast
- Control panel positive air pressurization

Applications

- Sand & gravel
- Blasted rock
- River rock
- C & D waste
- Foundry waste
- Processed ores
- Processed minerals

Output Potential

Up to 300tph (330 US tph)*

Product Conveyor

Width: 1000mm (39")
Discharge height: 3.30m (10'10")

Crusher

Automax® cone crusher with all roller bearing design
Size (head diameter): 1150mm (45")
Concave standard: Medium coarse
Min CSS: 18mm (0.7")*
Max feed size: 180mm (7.1")*

Hopper

Wear resistant feed hopper with crash bars
Length: 3.5m (11'6")
Width: 2.25m (7'5")
Capacity: 6m³ (7.8yds³)



1150 MAXTRAK

Weight (Est)	42,900kg (94,578lbs) (no options)
Transport width	3m (9'10")
Transport length	16.9m (55'5")
Transport height	3.6m (11'10")
Working width	4.9m (16'1")
Working length	16.4m (53'10")
Working height	5.6m (18'4")



*Depends on application
Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3/Stage 3A, Tier 4/Stage 3B, Tier 4F / Stage 4).

Power Unit

Tier 3/Stage 3A:
CAT C13 ACERT 328kW (440hp)
Tier 4F/Stage 4:
Scania DC13 84A 331kW (444hp)
Fuel tank capacity: 1000 L (264 US gal)

Feed Conveyor

Width: 1200mm (47")
Over and under belt metal detector

Tracks

Width: 500mm (19.7")

